



NANOSTUCCO 3D-MULTIFOIL SHI13

ITEM SPECIFICATIONS

High-performance, 3-layer desolidarising membrane with non-woven fabric, polyethylene membrane with a marked 3D shock-absorbing profile and polypropylene surface suitably fibreglassed for improved adhesion. Specific for waterproofing even overlapping on balconies, terraces and horizontal surfaces.

PREPARATION & LAYING

Bond the membrane on the surface to be waterproofed with NANOSTUCCO BASE. Apply NANOSTUCCO BASE as a normal tile adhesive and apply the membrane, previously cut to size, on the fresh product. To improve performance, crush with a heavy roller. Do not overlap the sheets but seal them with polyethylene waterproof band and NANOSTUCCO JOINT. Two hours before application, it is essential to unroll the membrane in order to relieve the tensions accumulated by it.

FEATURES

Aspect: 3-layer membrane roll

Dimensions: m 1 x 30
thickness mm 3

WARNING

The requirements and the guidelines herein are to be considered purely indicative and corresponding to our everyday best experience. We therefore recommend carrying out the tests in order to verify that the product corresponds to what is actually required and expected. We, as producers, do not assume any responsibility about how, when and where our products are applied except for the constant quality of the material.

TECHNICAL CHARACTERISTICS

QUICK INSTALLATION

NANOSTUCCO 3D-MULTIFOIL is easy and quick to install and allows large surfaces to be waterproofed quickly and to immediately secure the surfaces to be waterproofed, even when overlapping on balconies, terraces and horizontal surfaces of any size and for the realization of complete waterproofing cycles of even less than 5 mm.

VERSATILE

It can be used for waterproofing balconies, terraces and swimming pools, and indoors on heating floors. Once smoothed with 2 coats of NANOSTUCCO BASE, it is an excellent base for finishing with NANOSTUCCO cycles.

SAFE

NANOSTUCCO 3D-MULTIFOIL is totally desolidarising: it perfectly decouples the behaviour of the lower face from the upper one. When bonded with NANOSTUCCO BASE, it does not transmit the tensions to the floor and therefore reduces the risk of cracks on the following finish. Combined with polyethylene waterproof band and NANOSTUCCO JOINT, it allows large surfaces to be waterproofed without interruption.



FOR INDOOR
& OUTDOOR USE



PACK OF
1 ROLL



TO BE APPLIED
AT TEMPERATURE
FROM 5°C TO 35°C



USE PERSONAL
PROTECTIVE
EQUIPMENT

- safe
- useful as a barrier on damp floors on the ground floor
- high crack-bridging
- waterproof in any situation
- desolidarising
- fast securing of the works