



# NANOSTUCCO BAND SHI14

## ITEM SPECIFICATIONS

Waterproof polyethylene tape with a non-woven polypropylene fabric on both sides. Designed to ensure continuity between the joints of the rolls of NANOSTUCCO 3D-MULTIFOIL. Specific for use with NANOSTUCCO JOINT.

## PREPARATION & LAYING

Bond the NANOSTUCCO BAND waterproof tape with the specific product NANOSTUCCO JOINT at the perimeter joints and to join adjacent sheets of NANOSTUCCO 3D-MULTIFOIL membrane in waterproofing works on balconies and terraces before applying the NANOSTUCCO cycles.

## FEATURES

Aspect: non-woven fabric roll

Dimensions: mm 150 x m 30  
thickness mm 0,42

## WARNING

The requirements and the guidelines herein are to be considered purely indicative and corresponding to our everyday best experience. We therefore recommend carrying out the tests in order to verify that the product corresponds to what is actually required and expected. We, as producers, do not assume any responsibility about how, when and where our products are applied except for the constant quality of the material.

## TECHNICAL CHARACTERISTICS

NANOSTUCCO BAND is used to consolidate and give continuity to the waterproofing work carried out with the NANOSTUCCO 3D-MULTIFOIL cold waterproofing membrane. Its high adhesion, combined with that of NANOSTUCCO JOINT to bond it, guarantees the continuity of the waterproofing on the whole surface and on the edges. Perfect for making wall/floor connections or in correspondence with drain outlets.



FOR INDOOR  
& OUTDOOR USE



PACK OF  
1 ROLL



TO BE APPLIED  
AT TEMPERATURE  
FROM 5°C TO 35°C



USE PERSONAL  
PROTECTIVE  
EQUIPMENT

- for waterproofing balconies and terraces
- ease of use
- specific for NANOSTUCCO application cycles